

Type 3 Cylinders 23" Diameter Family

Fast Fill DGE

temperature compensated

26.1

34.8

40.3

Volume	300 Liter (10.62 ft ³)	400 Liter (14.12 ft ³)	463 Liter (16.35 ft ³)
GGE	26.3	35.0	40.6
DGE	23.1	30.8	35.7
Service Pressure	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)
Diameter	23.0 in	23.0 in	23.0 in
Length	62.5 in	82.4 in	90.0 in
Weight	305 lbs	370 lbs	390 lbs
Mount	strap	neck	strap

Gasoline and Diesel equivalence determined @ 24.8 MPa (3,600 psi) and 21°C Industry Average (IA) = 4.82 lb/GGE, DGE = .88*GGE IA

Winkelmann Flowform Technology - Fuel Systems

1525 Rancho Conejo Blvd., Suite 207

Thousand Oaks CA 91320 • USA

Ph: +1 (805) 278-8060 • Fx: +1 (805) 375-8090

www.wft-fuelsystems.com

Type 3 Cylinders 25" Diameter Family



Fast Fill DGE temperature compensated	28.6	40.6	46.2	49.2
Volume	327 Liter (11.55 ft ³)	465 Liter (16.42 ft ³)	530 Liter (18.72 ft ³)	563 Liter (19.88 ft ³)
GGE	28.7	40.8	46.5	49.4
DGE	25.3	35.9	40.9	43.5
Service Pressure	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)
Diameter	25.0 in	25.0 in	25.0 in	25.0 in
Length	60.0 in	80.0 in	90.0 in	93.5 in
Weight	310 lbs	413 lbs	465 lbs	484 lbs
Mount	neck	neck	neck	neck

Gasoline and Diesel equivalence determined @ 24.8 MPa (3,600 psi) and 21°C Industry Average (IA) = 4.82 lb/GGE, DGE = .88*GGE IA