

## Fast Fill DGE

Illenado con compensación de temperatura

**26.1**

**34.8**

**40.3**

Volúmen	300 Litro (10.62 ft <sup>3</sup> )	400 Litro (14.12 ft <sup>3</sup> )	463 Litro (16.35 ft <sup>3</sup> )
GGE	26.3	35.0	40.6
DGE	23.1	30.8	35.7
Pres. de Servicio	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)
Diámetro	23.0 in	23.0 in	23.0 in
Largo	62.5 in	82.4 in	90.0 in
Peso	305 lbs	370 lbs	390 lbs
Montaje	Correa	Correa	Correa

La equivalencia de Gasolina y Diesel determinada @ 24.8 MPa (3,600 psi) y 21°C Promedio de Industria (PI) = 4.82 lb / GGE, DGE = .88\* GGE PI

<b>Fast Fill DGE</b>	<b>28.6</b>	<b>40.6</b>	<b>46.2</b>	<b>49.2</b>
----------------------	-------------	-------------	-------------	-------------

llenado con compensación de temperatura

Volúmen	327 Litro (11.55 ft <sup>3</sup> )	465 Litro (16.42 ft <sup>3</sup> )	530 Litro (18.72 ft <sup>3</sup> )	563 Litro (19.88 ft <sup>3</sup> )
GGE	28.7	40.8	46.5	49.4
DGE	25.3	35.9	40.9	43.5
Pres. de Servicio	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)	3,600 PSI (250 Bar)
Diámetro	25.0 in	25.0 in	25.0 in	25.0 in
Largo	60.0 in	80.0 in	90.0 in	93.5 in
Peso	310 lbs	413 lbs	465 lbs	484 lbs
Montaje	Cuello	Cuello	Cuello	Cuello

La equivalencia de Gasolina y Diesel determinada @ 24.8 MPa (3,600 psi) y 21°C Promedio de Industria (PI) = 4.82 lb / GGE, DGE = .88\* GGE PI